


REVEL WHEELS

Thanks for purchasing Revel Wheels or Revel Rims from us!
If you're building these wheels yourself, there are a few things we'd like for you to know:




27.5"

ERD - 548 mm

Rim Weight - 460g

Tire Size: 27.5"x 2.3" - 2.6"



29"

ERD - 592 mm

Rim Weight - 485g


Tire Size: 29"x 2.3" - 2.6"

RIM SPECS:

Symmetric Angled Spoke Hole Drilling

Fully Recyclable

Lifetime Guarantee




29"

ERD - 592 mm

Rim Weight - 435g

Tire Size: 29"x 2.2" - 2.4"



700c

ERD - 592 mm

Rim Weight - 400g

Tire Size: 700c x 32mm - 47mm

* weights and dimensions subject to variation due to manufacturing process allowances

OUR RECOMMENDED BUILD SPECS FOR MAXIMUM STROKE:

Ideal Spoke Tension - 110kg

Safe Spoke Tension Range - 100-120kg

2x or 3x spoke lacing only for RW27s and RW30s, 2x spoke lacing only for RW23s

-ALWAYS BUILD WITH INCLUDED SAPIM MG WASHERS-

ONLY USE BRASS SAPIM SPHERICAL HEAD NIPPLES: EITHER DOUBLE SQUARE OR POLYAX

Please reach out to Revel Sales and Service with any questions regarding build criteria



This Card is 100% Recyclable